

Kit d'outils pour amortisseur et suspension Macpherson,

Most suspension strut top fixings require the top of the strut to be held while the fixing nut is removed. The design of the tools required for this operation vary considerably from manufacturer to manufacturer and often even across model ranges. The 7673 has been specifically designed for repairing and replacing shock absorbers including macpherson strut type assemblies.



Additional Information

- Comprend : 1 cliquet traversant à carré 1/2" (21 mm hexagonal) ; 2 rallonges magnétiques à carré 1/2" - 95 mm et 190 mm ; 1 rallonge spéciale 120 mm.
- 3 adaptateurs de douilles à fente : 5 mm x 8 mm, 6 mm x 8 mm, 8 mm x 11 mm.
- 7 douilles traversantes 16 mm, 17 mm, 18 mm, 19 mm, 21 mm, 22 mm, 24 mm x 78 mm de longueur.
- 6 embouts à tige hexagonaux 8 mm : hexagonal 5 mm, 6 mm, 7 mm, 8 mm, embout cannelé M10 et étoile T50 et 4 adaptateurs de douilles hexagonaux : 7 mm, 8 mm, 9 mm, 10 mm.
- La conception de la douille traversante combinée à la douille de rallonge spéciale permet l'accès jusqu'à une profondeur de 188 mm.

<http://lasertools.co.uk/product/7673>



